



DOME & LOW ANGLE



COMPARISON SHEET



MODULAR RINGLIGHT



SDOME II & LOW ANGLE II

<p>80mm OR 130mm</p>	<p>DIMENSIONS</p>	<p>80mm OR 130mm</p>
<p>R-C OR W-IR Red & Cyan OR White & IR</p>	<p>COLOURS</p>	<p>Red Blue Green White IR</p>
<p> 4 QUADRANTS</p>	<p>QUADRANTS</p>	<p>‘Not applicable’</p>
<p>x2.5 Brightness measured on the ring – White colour</p>	<p>BRIGHTNESS</p>	<p>x1 Brightness measured on the ring – White colour</p>
<p> 10µs &  10µs</p>	<p>RESPONSIVENESS</p>	<p> 10µs &  10µs</p>
<p>Continuous 50 kHz & Strobe 310 kHz</p>	<p>MAX FREQUENCY</p>	<p>‘Not applicable’</p>
<p>UP TO x4 </p>	<p>OVERDRIVE</p>	<p>‘Not applicable’</p>
<p>0V: 100% & 10V: 30%</p>	<p>DIMMING</p>	<p>‘Not applicable’</p>
<p>M12 5 pins & M12 8 pins</p>	<p>WIRING</p>	<p>M12 4 pins</p>
<p>manual & remote</p>	<p>CONTROL</p>	<p>remote</p>
<p> IP65</p>	<p>IP PROTECTION</p>	<p>IP30</p>
<p>Power & Strobe</p>	<p>LED INDICATORS</p>	<p>‘Not applicable’</p>